



Landmark's Sunlight Readable Open Frame Displays

All of Landmark's Open Frame Units include an LCD Module, VHB Backlight, Inverter, Controller Card, OSD Kit, and PSU

Part Number	LMK190	LMK192	LMK222		LMK181		LMK194	LMK198	LMK225	LMK199	LTK201	
Size (Diagonal)	12.1"	15.0"	17.0"		19.0"		20.0"	26.0"	32"	40"	42.0"	
Brightness	1650 nits	2250 nits	1300 nits		1450 nits		1400 nits	1500 nits	1350 nits	1000 nits	870 nits	
Contrast Ratio	800:1	800:1	600:1		600:1		750:1	800:1	1700:1	2000:1	800:1	
Viewing Angles	80/80/80/80 R / L / U / D	70/70/70/70 R / L / U / D	70/70/70/60 R / L / U / D		80/80/80/80 R / L / U / D		75/75/65/65 R / L / U / D	80/80/55/55 R / L / U / D	85/85/85/85 R / L / U / D	89/89/89/89 R / L / U / D	89/89/89/89 R / L / U / D	
Aspect Ratio	4:3	4:3	5:4		5:4		16:9	16:9	16:9	16:9	16:9	
LCD Resolution	XGA 1024 x 768	XGA 1024 x 768	SXGA 1280 x 1024		SXGA 1280 x 1024		WXGA 1366 x 768	WXGA 1366 x 768	WXGA 1366 x 768	WXGA 1366 x 768	WXGA 1366 x 768	
Inverter / LED Driver	BI218	BI224B	BI320A		BI330C		BI320A	BI528	BI520 + BI522	Backlight Inverter	Backlight Inverter	
LCD Controller	MG22	MG21	MG22	MG21	MG22	MG21	MG22	MG22	MG22	MG22	MG22	MG21
Video Inputs	15 pin D-sub DVI	VGA DVI	15 pin D-sub DVI 4pin Min Din RCA	VGA DVI	15 pin D-sub DVI 4pin Min Din RCA	VGA DVI	15 pin D-sub 4 pin Min Din RCA	15 pin D-sub 4pin Min Din RCA	15 pin D-sub DVI optional 4pin Min Din RCA	15 pin D-sub DVI optional 4pin Min Din RCA	15 pin D-sub DVI 4pin Min Din RCA	VGA DVI
Power Required	12V, 3A	12V , 4.4A	12V , 4.5A		12V , 7.3A		12V , 5.5A	24V , 5A 12V , 1A	24V, 7A 12V, 1A	24V , 8.7A 12V , 1 A	24V , 7.1A 12V, 1A	
Dimension (in.)	7.9 x 10.4 x 0.9 H x W x D	9.9 x 12.9 x 1.8 H x W x D	11.6 x 14.1 x 2.0 H x W x D		13.0 x 15.9 x 1.89 H x W x D		18.6 x 10.9 x 2.0 H x W x D	14.69 x 24.65 x 2.3 H x W x D	17.72 x 29.92 X 2.5 H x W x D	20.64 x 35.89 x 2.5 H x W x D	22.68 x 38.70 x 2.5 H x W x D	